

The FlexOrder / HP Range by PulseGuard

Inch / Standard

Ordering			For Press. Pulse Interception and Accumulation Connections	For Flow Fluctuation reduction by Accumulation, Only Connection			Specification Without Fittings			Price One Piece \$s US	Service		
Type	Vol In ³	DP @ 200F PSI	To Pump / To Sys	Single Flange face ANSIB16.5	"O" Ring Face		L in	D in	lbs		Spares Kit		
Flo-TW ^{**} _{SS}	1.5	2000	1/8"MM x 1/8"MM	Or Threaded 3/8" FNPT			5.3	6	24		DW85		
Flo-TW _{SS}	3	2000	1/4"MM x 1/4"MM				1/2" FNPT	5.3	6.3	31		DW93	
Flo-TW _{SS}	7	2000	3/8"MM x 3/8"MM				3/4" FNPT	5.3	6.5	33		DW113	
Flo-TW _{SS}	10	2000	1/2"MM x 1/2"MM				1.0" FNPT	5.3	7	35		DW127	
Flo-TW _{SS}	0.5	3000	1/8"MM x 1/8"MM				1/8" FNPT	3.5	5.3	12		DW65	
Flo-TW _{SS}	1.6	6000	1/8"MM x 1/8"MM				1/4" FNPT	5.6	6.3	24		DW85	
Flo-TW _{SS}	3.1	4000	1/4"MM x 1/4"MM				1/2" FNPT	5.6	6.3	33		DW93	
Flo-TW _{SS}	3.2	6000	1/4"MM x 1/4"MM				1/2" 2500#	4x0.75"on 3.5"	5.6	6.3	37		DW93
Flo-TW _{SS}	11	7000	.50 NF x .50 F				1/2" 2500#	4x0.75"on 3.5"	6.75	8	79		DW127
CONNECTIONS ABOVE DIRECT THREADED													
Flo/"O" _{SS}	15	6000	.50 NF x .50 NF	3/4" 2500#	4x0.75"on 3.75"	7.5	10	130		DW145			
Flo/"O" _{SS}	25	5850	.75 NF x .75 NF	3/4" 2500#	4x0.75"on 3.75"	8.25	10.5	190		DW160			
Flo/"O" _{SS}	40	5750	1.00NF x 1.00 NF	1" 2500#	4x0.875"on 4.25"	9.5	12	230		DW175			
CONNECTIONS ARE ON PIPING BASE BLOCKS													
SIZES BELOW ARE NOT ALWAYS INVENTORY													
Flo/"O" _{SS}	61	5500	1.00 NF x 1.00NF	1" 2500#	4x0.875"on 4.25"	10	12.5	299		DW187			
Flo/"O" _{SS}	80	5250	1.25 NF x 1.25 NF	1 1/2" 2500#	4x1.25"on 5.75"	11	13.5	350		DW200			
Flo/"O" _{SS}	122	5000	1.50 NF x 1.50 NF	2" 2500#	4x1"on 6.75"pcd	11.5	14	400		DW223			
Flo/"O" _{SS}	180	4500	1.50 NF x 1.50 NF	2 1/2" 2500#	4x1.125"on 7.75"	12.5	16	550		DW265			
SIZES BELOW ARE ONLY ASSEMBLED TO ORDER													
Flo/"O" _{SS}	240	4000	2.00MW x 2.00MW	2 1/2" 2500#	4x1.125"on 7.75"	13	17	675		DW280			
Flo/"O" _{SS}	300	3500	2.50MW x 2.50MW	3" 2500#	4x1.25"on 9"pcd	15.2	18	800		DW305			
Flo/"O" _{SS}	400	3000	3.00MW x 3.00MW	4" 1500#	4x1.25"on 9.5"pcd	17	20	1200		DF345			
Flo/"O" _{SS}	800	2500	3.00MW x 3.00MW	5" 1500#	4x1.5"on 11.5"pcd	20	30	3000		DF450			