

The PipeHugger /LP Range by PulseGuard

Inch / "Standard"

ORDERING		DP @ 200F PSI	Connections		1 Connection Ansi B16.5 Largest Bolt Circle Diam	Specification			Price one. Piece \$	Spares Kit SK/-?=Elast EP, N(Buna), Hyp, V(Fluoro)
Liquid in Bladder Gas in Steel drive bonnet	In 3		To pump x To system			L in	D in	lbs		
Peg-TW-ss**	10	1450	1/8"x1/8"	NF	3/4" 600#	5.2	3/	5		D64y42 ?
Peg-TW-ss	20	1450	3/8"x3/8"	NF	1/2" 150#	5.2	4	10		D85y40 ?
Peg-TW-ss	40	1450	1/2"x3/8"	NF	1/2" 300#	6.7	5.5	20		D115y64 ?
Peg-TW-ss	61	750	3/4"x1/2"	NF	1.0" 600#	6.9	6	18		D125y65 ?
Peg-TW-ss	92	600	1.0"x3/4"	NF	1.5" 300#	6.9	6.5	24		D145y75 ?
Peg-TW-ss	183	600	1.0"x1.0"	NF	2.5" 300#	8.5	8.5	37		D191y65 ?
Peg-TW-ss	366	425	1.5"Mx1.0"	NF	4.0" 300#	9.4	10.4	55		D244y113 ?
Peg-TW-ss	733	365	2"NMx2"	NM	5.0" 150#	10.1	12.7	81		ND285y128?
Peg-TW-ss	1000	365	3"NMx2"	NM	6.0" 150#	11.8	14	114		ND328y123?
Peg-TW-ss	1650	365	4"Wx4"W	37.5 ⁰	8.0" 150#	16	16	163		ND368y176?
Peg-TW-ss	2200	365	5"Wx5"W	37.5 ⁰	10" 150#	22	20	220		ND450y120?