

# The all ss Dual Use PipeGuard - "TW"

## & the all ss slimline - "SL" Ranges by PulseGuard

ORDERING			Price One Piece \$ US	US DP @ 200F PSI	For Pulse Intercept. Twin Connections		Flow Smoothing Single		Specification Inches			Service "SK" Spares Kit ? = Nat, N(Buna), EP, V(Fluoro etc
Type	Vol In3	EN 5500 PMax "psi"			to pump / to system	45 x45	NPT	ANSI B 16.5	L in	D in	lbs	
PIG -TW /	1	6000		3500	1/8"x1/8"	NF			4.1	1.75	2.6	B24x50 ?
PIG -SL /	2	3000		1800	1/4"x1/4"	NF	3/8"		6.5	1.37	3.3	B24x80 ?
PIG -TW /	6	2175		1250	3/8"Fx1/4"	NF			6	2.37	3.7	B44x75 ?
PIG -SL /	10	2900		1700			1/2"		8.7	1.9		B36x120 ?
PIG -TW /	15	2175		1250	1/2"Fx3/8"	NF			7.5	2.75	12	B57x98 ?
PIG -SL /	20	2537		1500			3/4"		10.4	2.38		B50x160 ?
PIG -TW /	30	2175		1250	1/2"Fx3/8"	NF			10.5	2.75	13	B57x173 ?
PIG -TW /	30	2175		1250	3/4"Fx1/2"	NF	1"		11.4	2.87	11	B62x175 ?
PIG -TW /	40	2175		1250	3/4"Fx1/2"	NF			12.5	2.87	15	B62x207 ?
PIG -SL /	45	2900		1700			3/4"		12.4	2.88		B62x207 ?
PIG -TW /	60	1250		750	3/4"Fx3/4"	NF		1/2"300#	14.5	3.46	37	B72x255 ?
PIG -TW /	60	1500		900	1"Fx1"	NF	1.5"M	1" 600 #	11	4.49	55	B98x131 ?
PIG -SL /	70	2537		1500			1"		16.9	3.5	25	B72x315 ?
PIG -TW /	75	1250		750	3/4"Fx3/4"	NF		1/2"300#	17.5	3.46	48	B72x315 ?
PIG -TW /	100	1500		900	1.25"Mx1"	NF	1.5"M	1" 600 #	15	4.49	55	B98x232 ?
PIG -SL /	110	2175		1300			1.25"M		15.9	4.0	31	B86X275 ?
PIG -TW /	120	1250		750	1.5"Mx1.5"	NM	2"M	2" 300 #	10.8	6.7	66	B139x105 ?
PIG -SL /	146	2175		1300			1.5"M		17.3	4.5	40	B98x300 ?
PIG -TW /	180	1500		900	1.5"Mx1.5"	NM	3"M	1.5" 600#	14.3	5.55	79	B123x267 ?
PIG -TW /	200	1500		900	1.5"Mx1.5"	NM	3"M	1.5" 600#	18.4	5.55	88	B123x295 ?
PIG -SL /	260	2537		1500			2"M		19.7	5.56	50	B110x360 ?
PIG -TW /	250	1500		900	2"Mx2"	NM		1.5" 600#	20.8	5.55	99	B123x357 ?
PIG -TW /	244	1250		750	3"Mx2"	MW	3"M	2" 300 #	13.7	6.7	103	B139x212 ?
PIG -TW /	305	1250		750	3"Mx2"	MW	3"M	2" 300 #	18	6.7	123	B139x325 ?
PIG -SL /	366	2537		1500			3"M	+Flg extra	22	6.63	70	B139x420 ?
PIG -TW /	488	1250		750	3"Mx2"	MW	3"M	2" 300 #	22	6.7	141	B139x420 ?
PIG -TW /	693	1500		900	3"Mx3"	MW	4"W	+Flg4"300#	24	8.6	211	B195x360 ?
PIG -SL /	854	2175		1300			3"M	+Flg extra	29	8.63	240	B184x580 ?
PIG -TW /	1220	1000		600	3"Mx3"	MW	4"W	+Flg5"300#	30	10.7	389	B230x500 ?
PIG -TW /	2135	1000		600	4"Mx4"	MW	5"W	+Flg6"300#	36	12.7	712	B260x600 ?
PIG -TW /	3050	1000		600	5"Mx5"	MW	6"W	+Flg8"300#	42	14	740	B300x700 ?